



AlumaSAFE™ 50

Aluminum Repair Isolation Station




AlumaSAFE 50 Max - Cable Suspended
Shown with clearview curtains

- ➔ Confinement of Contaminants
- ➔ A Cleaner Work Environment
- ➔ Instant Separation of Work Area
- ➔ Protection from Sparks & Hazardous Debris

Aluminum Repair requires isolated work areas to prevent cross contamination. AlumaSAFE Aluminum Repair Isolation Stations are designed to contain the vehicle and required tools within one working area.

STANDARD FEATURES

- Weldview or Clearview Curtains Available
- Curtains are NFPA 701 Compliant
- Includes:
 - Curtains that allow openings at either end
 - All hardware straight and curve tracks and roller hooks for mounting curtains.
 - Installation Instructions
- Suspended from ceiling (cabling not included) or column supported
- Lighted models include 4-tube interior accessible light fixtures with T-8 energy efficient fluorescent bulbs



Length	Dimensions		Light Fixtures/Bulb Count		
	Width	Height	Curtains Only	w/ Light Ring	w/ Ceiling & Lights
27'	14'	9'	0/0 bulbs	6/24bulbs	6/24bulbs
31'	14'	9'	0/0 bulbs	6/24bulbs	7/28bulbs
27'	16'	12'	0/0 bulbs	6/24bulbs	6/24bulbs
31'	16'	12'	0/0 bulbs	6/24bulbs	7/28bulbs

AlumaSAFE 50 - Curtain Structure



AlumaSAFE 50 Plus- Curtain Structure with Lights



AlumaSAFE 50 Max - Curtain Structure with Lighted Ceiling

